

Technical Characteristics

Wrapping programs model MYTHO A:	5,7" TOUCH screen operating panel with 7 Programs
Turntable diameter:	2000 mm (Pallets 1000 x 1200 mm)
Optional turntables:	2150 / 2300 / 2700 / 2800 mm
Turntable Maximum loading weight:	2000 Kg
Adjustable turntable rotation speed facilitated by frequency changer:	From 5 to 15 rpm *
Soft stop / start facilitated by frequency changer:	STANDARD SUPPLY
Precise turntable phase stopping at cycle end:	STANDARD SUPPLY
Carriage braking system:	FE (FTL = Magnetic brake force to load)
Standard Wrapping height:	2400 mm
Optional wrapping height:	-
Photocell detection of load height:	STANDARD SUPPLY
Adjustable Spool carriage speed facilitated by inverter:	From 1,3 up to 5,4 m/min
Upwards Spool carriage speed:	Independently settable
Downwards Spool carriage speed:	Independently settable
Standard conveying transport height:	From 450 up to 550mm
Total installed power:	5 Kw
Standard voltage:	400 V - 50/60 Hz – 3 Ph + N + T
Electrical and motor protection system:	IP 54
Pneumatic pressure:	6 bar
Output capacity:	45 Pallets per Hours **

* Depending on configuration

** Depending on film quality and working environment:

Wrapping conditions and pallet dimensions have an influence on the Max output capacity

Stretch film specifications

Recommended thickness for stretch-film	From 10 to 30 µm
--	------------------

Available options

Different transport heights	✓
Available for OEM / LINE Builders	✓
Infeed / Outfeed conveying systems	✓
Top pressure plate round / rectangular	✓
Power Pre-Stretch One Motor PRS	✓ (Included gears 150% / 200% / 250%)
Power Pre-Stretch Two Motors PS	✓
Roping system	✓